

1K WATER BASE POLYMER SEALER

DESCRIPTION

MAGIECHEM 119 is an acrylic / urethane sealer with excellent water resistant. It is a high quality transparent and high penetrating sealer for concrete, masonry and other porous surfaces.

MAGIECHEM 119 can be used as cure and sealing membrane on fresh concrete.

MAGIECHEM 119 can also be applied on existing concrete surfaces to provide a durable film and resistance.

ADVANTAGE

- Good abrasion resistance
- Excellent adhesion on concrete
- Stains resistant and dust free
- Can be used on vertical and horizontal surfaces
- Meets the standard curing and sealing
- Compatible with several coatings and adhesives
- Easy to apply

APPLICATION

The surface must be free from all contaminants such as grease, oil, tire marks, etc. . .

Chemical preparation or mechanical cleaning is recommended, depending on the surface conditions

INSTRUCTIONS

- Mix the material before use.
- Freshly poured concrete:
Apply a uniform layer about 1 or 2 hours after finishing operations
- Existing Concrete:
Apply 1 or 2 coats of sealer, depending on surface porosity.

PRECAUTIONS

- Consult MSDS before use
- Do not apply the material if the temperature is below 13 °C (55 °C).



MAGIECHEM



1K WATER BASE POLYMER SEALER

TECHNICAL INFORMATION

Application: Brush, roller, spray or push broom

Number of Coats: 1 or 2 coats according to the surface porosity.

Recovery: 4 a 6 hours

Cure: 24 hours

Cleaning Solvent: Water

C.O.V.: 32 g/L (1 and 5 gallons US)

Shelf Life: 1 year in original unopened container Packing: 3.78 liters and 18.9 liters (200 liters)

For assistance, consult a representative of MAGIECHEM products.

TECHNICAL SERVICES AND WARRANTY

The information contained in this data sheet is based on trials that we believe valid. However, when using, the conditions of application are beyond our control, the seller and / or the manufacturer disclaim any responsibility except to replace the product proves defective.



MAGIECHEM

SURFACE/GALLON					
Thickness (mils)	1	4	8	10	20
Gallon/sq.ft	1600	400	200	160	80

